

The secret for a successful pool

www.hayward.fr/en

CONTINUE THE EXPERIENCE ON: facebook.com/hayward.fr You Tube HaywardPoolEurope

ONLINE SERVICES Free extended warranty Free subscription to the newsletter The heat pump configurator Online savings simulator On-line expert Spare parts catalogue

HEAT PUMPS

HAYWARD

Heat

Inpu

Curr

Pow

Defro

Com

Fan

Rota

Fan

Pres

Pres (at 1

Wate

Nom

Wate

Unit EER, Gas Wint

Heating Priority Function

LIGHTING

EnergyLine Pro all season

The all season EnergyLine Pro can operate up to -12°C, this heat pump remains the best heating solution no matter the season or the weather conditions.

Les PLUS

- + Ideal product for inside pools and colder areas
- + Automatic defrosting by cycle inversion
- + Night program for lower operating noise
- + Automated and reversible function in order to heat and cool the pool in case of excessive heat

Intuitive touch

Simplified electrical connection.



| cription | Unit | ENP6MAS | ENP6TAS | ENP7TAS |
|---------------------------|----------|----------------|----------------|----------------|
| ting Capacity* | Kw/BTU/h | 17,2 58 741 | 17,5 59 765 | 22,5 76 841 |
| it Power* | Kw | 3,5 | 3,5 | 4,7 |
| rent* | А | 16,2 | 7,7 | 9,7 |
| ver Supply | V/Ph/Hz | 230/1/50 | 380/3/50 | 380/3/50 |
| osting mode | | Reverse cycle | | |
| npressor | | Copeland | | |
| Quantity | | 2 | | |
| ation speed of fan | RPM | 820 | 899 | 925 |
| Direction | | Horizontal | | |
| ssure noise level (at 1m) | dB(A) | 58,5 | 60,5 | 61,2 |
| ssure noise level IOm) | dB(A) | 41,8 | 43,8 | 44,5 |
| er Connection | mm | 50 | | |
| ninal water flow | m³/h | 6,5 | 6,5 | 8 |
| er Pressure drop (max) | kPa | 21 | 14 | 21 |
| Dimensions(L/L/H) | mm | 1138/470/1264 | | |
| * | | 4,85 | 5 | 4,74 |
| | | R410A/2,3 | R410A/2,3 | R410A/2,8 |
| ter Cover | | Yes | | |

⁽¹⁾ 2 years warranty + 1 year extra when the product is purchased from a Totally Hayward dealer.



FILTERS

• Thermal performance according to the rating test conditions of the norme NF-414 - Dry Air 15°C HR 71 % Water temperature 26°C Nominal water flow R410A (50% R125:50%R32)

WATER TREATMENT

CLEANERS

Yes

HEAT PUMPS

to optimize heat transfer. **NATURALLY HAYWARD®**

Long-life PVC-Titanium Heat Exchanger: to prevent corosion from chlorine and salt. Double flow design

aywa

All season heat pump with an integrated electronic cycle reversing defrost management system that will allowed

the heat pump to work at a temperature of -12°C. Extremely guiet operation: on the all-seasons models,

the speed of the ventilator automatically varies according to the needs of the machine.

In the middle of summer when the heat pump benefits from weather conditions allowing it to

Easy-to-use: its intuitive touch screen means adjusting the settings and usage are child's play.

Ease of installation and maintenance: 50 mm union

supplied, external electrical trap door, drainage cap for wintering, wintering protection cover.

provide optimum yield, it will slow down the rotation of its blades and continue to heat your pool silently.

COP superior to 4.

2 YEARS

EFFICIENCY

EASE OF USE

EXTRA DURABILITY

PUMPS